

INTUMET™ FS3003 SOFT PUFF™ INTUMESCENT

Technical Data Sheet



Product Description:

INTUMET™ FS3003 is rubber matrix material beings intumescenting at relatively low temperatures where organic materials begin to emit combustibile and noxious gases. It expands gradually with moderate force and has sufficient reservoir capacity to continue intumescenting. INTUMET™ FS3003 is fibres and halogens free.

Test Certificate:

UL listed. Certificate Numer 061000-R18465
Standard for Safety : UL10C - Standard for Positive Pressure Fire Test of Door Assemblies
UBC7-2 (1997) - Fire test of Door Assemblies

Physical Properties:

Activation Temperature.....	250°F (121°C)
Expansion Volume.....	20 X
Expansion Pressure.....	27 PSI (.0187 N/mm ²)
Multi or controlled directional.....	yes
Stability after expansion.....	Very Good
Char.....	Hard
Flame-resistant.....	yes
Moisture-resistant.....	yes
Chemically inert / paintable.....	yes
Non-carcinogenic.....	yes
Long-life (no deterioration).....	yes
Odor-free.....	yes
Asbestos-free.....	yes
Color-standard.....	Black

Applications:

INTUMET™ FS3003 can be used for the following applications:

- Filling all gaps of escape doors exposed to extreme heat.
- Protecting fire door on oil rigs.

Specifications:

INTUMET™ FS3003 is available in various thickness (millimeter or inches) and in any color as special order. Red color available for European specification. Supplied in strips, with self-adhesive tape or aluminum backing.

STOCK SIZES : Thickness .062"(1.6mm), .125"(3.2mm), .250"(6.4mm)
Width .375"(9.5mm), .500"(12.7), .750"(19.1), 1.00"(25.4), 1.50"(38.1), 2.00"(50.8)

ZERO INTERNATIONAL, INC.

415 Concord Avenue, Bronx, NY 10455 • phone: 718-585-3230 • fax: 718-292-2243
www.zerointernational.com